



**GAUGE FACTORS LTD**  
Advanced Strain Gauge Systems

Towergate Ind Park, Colebrook Way,  
Weyhill Rd, Andover, Hants. UK SP10 3BB  
Tel: +44(0)1264 336396 Fax: +44(0)1264 336826  
email: sales@gaugefactors.com

Product: GAK8

## Safety data sheet.

### Section 1. Identification of the substance/mixture & of the Company/undertaking

#### 1.1. Product identifier.

Product Name Water based acrylic coating  
Product no. GAK 8

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against.

Identified uses. Industrial use. Professional use. Appliance protection. Tacking.

#### 1.3. Details of the supplier of the safety data sheet.

Supplier. Gauge Factors Ltd, 3 Towergate Ind Pk., Colebrook Way, Andover, Hants. SP10 3BB UK

#### 1.4. Emergency telephone number.

+44(0)1264 336396 between 8.30 - 4.30 Mon – Fr. Not 24 hours  
Email: sales@gaugefactors.com

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (EC 1272/2008)

Physical hazards	Not Classified
Health hazards	Not Classified
Environmental hazards	Aquatic Chronic 2 - H411

### 2.2. Label elements

#### Pictogram



Hazard statements	H411 Toxic to aquatic life with long lasting effects. EUH208 Contains 4,5-Dichloro-2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.
Precautionary statements	P273 Avoid release to the environment. P391 Collect spillage. P501 Dispose of contents/ container in accordance with national regulations.

### 2.3. Other hazards

## GAK8 Water based acrylic coating

This product does not contain any substances classified as PBT or vPvB.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

<b>2-Butoxyethanol</b> <span style="float: right;">5-10%</span>		
CAS number: 111-76-2	EC number: 203-905-0	REACH registration number: 01-2119475108-36-XXXX
<b>Classification</b> Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319		
<b>Dipropylene Glycol Monomethyl Ether</b> <span style="float: right;">&lt;1%</span>		
CAS number: 34590-94-8	EC number: 252-104-2	REACH registration number: 01-2119450011-60-XXXX
<b>Classification</b> Not Classified		
<b>4,5-Dichloro-2-octyl-2H-isothiazol-3-one</b> <span style="float: right;">&lt;1%</span>		
CAS number: 64359-81-5	EC number: 264-843-8	
M factor (Acute) = 100	M factor (Chronic) = 100	
<b>Classification</b> Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 2 - H330 Skin Corr. 1C - H314 Eye Dam. 1 - H318 Skin Sens. 1A - H317 STOT SE 3 - H335 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410		
<b>Kaolin</b> <span style="float: right;">&lt;1%</span>		
CAS number: 1332-58-7	EC number: 310-194-1	
<b>Classification</b> Not Classified		

## GAK8 Water based acrylic coating

<b>3-iodo-2-propynyl butylcarbamate</b>	<b>&lt;1%</b>
CAS number: 55406-53-6	EC number: 259-627-5
M factor (Acute) = 10	M factor (Chronic) = 1
<b>Classification</b>	
Acute Tox. 4 - H302	
Acute Tox. 3 - H331	
Eye Dam. 1 - H318	
Skin Sens. 1 - H317	
STOT RE 1 - H372	
Aquatic Acute 1 - H400	
Aquatic Chronic 1 - H410	

The full text for all hazard statements is displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
<b>Inhalation</b>	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
<b>Skin contact</b>	Rinse with water.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	Prolonged inhalation of high concentrations may damage respiratory system.
<b>Ingestion</b>	Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.
<b>Skin contact</b>	Prolonged contact may cause dryness of the skin.
<b>Eye contact</b>	May cause temporary eye irritation.

#### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Treat symptomatically.
-----------------------------	------------------------

## GAK8 Water based acrylic coating

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

**Suitable extinguishing media** The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up.

**Hazardous combustion products** Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

#### 5.3. Advice for firefighters

**Protective actions during firefighting** Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material.

#### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

#### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labelled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

## GAK8 Water based acrylic coating

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment.

**Advice on general occupational hygiene** Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store away from incompatible materials (see Section 10). Store in accordance with local regulations. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

**Storage class** Miscellaneous hazardous material storage.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### 2-Butoxyethanol

Long-term exposure limit (8-hour TWA): WEL 25 ppm 123 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 50 ppm 246 mg/m<sup>3</sup>

Sk

##### Dipropylene Glycol Monomethyl Ether

Long-term exposure limit (8-hour TWA): WEL 50 ppm 308 mg/m<sup>3</sup>

Sk

##### Kaolin

Long-term exposure limit (8-hour TWA): WEL 2 mg/m<sup>3</sup> respirable dust

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

### 8.2. Exposure controls

#### Protective equipment



## GAK8 Water based acrylic coating

<b>Appropriate engineering controls</b>	Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.
<b>Eye/face protection</b>	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.
<b>Hand protection</b>	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.
<b>Other skin and body protection</b>	Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.
<b>Hygiene measures</b>	Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.
<b>Respiratory protection</b>	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.
<b>Environmental exposure controls</b>	Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Liquid.
<b>Colour</b>	White.
<b>Odour</b>	Not known.
<b>Odour threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point</b>	Not available.
<b>Initial boiling point and range</b>	Not available.

## GAK8 Water based acrylic coating

Flash point	Not available.
Evaporation rate	Not available.
Evaporation factor	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Not available.
Other flammability	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Not available.
Bulk density	1.03 kg/l
Solubility(ies)	Not available.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	180-220 mPa s @ 23°C
Explosive properties	Not considered to be explosive.
Oxidising properties	Does not meet the criteria for classification as oxidising.

### 9.2. Other information

#### SECTION 10: Stability and reactivity

##### 10.1. Reactivity

Reactivity See the other subsections of this section for further details.

##### 10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

##### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions No potentially hazardous reactions known.

##### 10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

##### 10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

##### 10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

#### SECTION 11: Toxicological information

##### 11.1. Information on toxicological effects

## GAK8 Water based acrylic coating

### Acute toxicity - oral

Notes (oral LD<sub>50</sub>) Based on available data the classification criteria are not met.

ATE oral (mg/kg) 27,281.25

### Acute toxicity - dermal

Notes (dermal LD<sub>50</sub>) Based on available data the classification criteria are not met.

ATE dermal (mg/kg) 17,187.5

### Acute toxicity - inhalation

Notes (inhalation LC<sub>50</sub>) Based on available data the classification criteria are not met.

ATE inhalation (vapours mg/l) 171.88

### Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

### Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

### Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

### Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

### Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

### Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

### IARC carcinogenicity

Contains a substance which may be potentially carcinogenic. IARC Group 3 Not classifiable as to its carcinogenicity to humans.

### Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -  
development

Based on available data the classification criteria are not met.

### Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

### Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

### Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

### General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

### Inhalation

Prolonged inhalation of high concentrations may damage respiratory system.

### Ingestion

Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.

### Skin contact

Prolonged contact may cause dryness of the skin.



## GAK8 Water based acrylic coating

Eye contact	May cause temporary eye irritation.
Route of entry	Ingestion Inhalation Skin and/or eye contact
Target organs	No specific target organs known.

### 2-Butoxyethanol

#### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub>  
mg/kg) 1,746.0

Species Rat

Notes (oral LD<sub>50</sub>) REACH dossier information. Harmful if swallowed.

ATE oral (mg/kg) 1,746.0

#### Acute toxicity - dermal

Notes (dermal LD<sub>50</sub>) cATpE: Converted Acute Toxicity Point Estimate. Harmful in contact with skin.

ATE dermal (mg/kg) 1,100.0

#### Acute toxicity - inhalation

Notes (inhalation LC<sub>50</sub>) cATpE: Converted Acute Toxicity Point Estimate. Harmful if inhaled.

ATE inhalation (vapours  
mg/l) 11.0

#### Skin corrosion/irritation

Animal data Dose: 0.5 mL, 4 hours, Rabbit Erythema/eschar score: Well defined erythema (2).  
Oedema score: No oedema (0). REACH dossier information. Irritating.

#### Serious eye damage/irritation

Serious eye  
damage/irritation Dose: 0.1 mL, 24 hours, Rabbit Causes serious eye irritation.

#### Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. REACH dossier  
information. Based on available data the classification criteria are not met.

#### Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative. REACH dossier information. Based on available data the  
classification criteria are not met.

Genotoxicity - in vivo Chromosome aberration: Negative. REACH dossier information. Based on available  
data the classification criteria are not met.

#### Carcinogenicity

Carcinogenicity NOAEC 125 ppm, Inhalation, Mouse REACH dossier information. Based on  
available data the classification criteria are not met.

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

#### Reproductive toxicity

Reproductive toxicity -  
fertility Two-generation study - NOAEL 720 mg/kg/day, Oral, Mouse P REACH dossier  
information. Based on available data the classification criteria are not met.

GAK8 Water based acrylic coating

Reproductive toxicity - development      Maternal toxicity: - NOAEL: 50 ppm, Inhalation, Rabbit REACH dossier information. Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure      NOAEL <69 mg/kg/day, Oral, Rat REACH dossier information. Based on available data the classification criteria are not met.

4,5-Dichloro-2-octyl-2H-isothiazol-3-one

Acute toxicity - oral

ATE oral (mg/kg)      500.0

Acute toxicity - dermal

ATE dermal (mg/kg)      1,100.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> dust/mist mg/l)      0.26

Species      Rat

ATE inhalation (dusts/mists mg/l)      0.26

3-iodo-2-propynyl butylcarbamate

Acute toxicity - oral

ATE oral (mg/kg)      500.0

Acute toxicity - inhalation

ATE inhalation (gases ppm)      700.0

ATE inhalation (vapours mg/l)      3.0

ATE inhalation (dusts/mists mg/l)      0.5

**SECTION 12: Ecological Information**

12.1. Toxicity

Toxicity      Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.

2-Butoxyethanol

Toxicity      Aquatic toxicity is unlikely to occur. Based on available data the classification criteria are not met.

Acute toxicity - fish      LC<sub>50</sub>, 96 hours: 1474 mg/l, Onchorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates      EC<sub>50</sub>, 48 hours: 1550 mg/l, Daphnia magna

Acute toxicity - aquatic plants      EC<sub>50</sub>, 72 hours: 911 mg/l, Pseudokirchneriella subcapitata

GAK8 Water based acrylic coating

Chronic toxicity - fish early life stage NOEL, 21 days: >100 mg/l, Brachydanio rerio (Zebra Fish)

Chronic toxicity - aquatic invertebrates NOEC, 21 days: 100 mg/l, Daphnia magna

Dipropylene Glycol Monomethyl Ether

Acute toxicity - fish LC<sub>50</sub>, 96 hours: > 1000 mg/l, Poecilia reticulata (Guppy)

4,5-Dichloro-2-octyl-2H-isothiazol-3-one

Acute aquatic toxicity

LE(C)<sub>50</sub> 0.001 < L(E)C<sub>50</sub> ≤ 0.01

M factor (Acute) 100

Chronic aquatic toxicity

M factor (Chronic) 100

3-iodo-2-propynyl butylcarbamate

Acute aquatic toxicity

M factor (Acute) 10

Chronic aquatic toxicity

M factor (Chronic) 1

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

2-Butoxyethanol

Persistence and degradability The substance is readily biodegradable.

Biodegradation Water - Degradation 90.4%: 28 days

Dipropylene Glycol Monomethyl Ether

Persistence and degradability The product is readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

2-Butoxyethanol

Bioaccumulative potential Bioaccumulation is unlikely.

Partition coefficient log Kow: 0.81

Dipropylene Glycol Monomethyl Ether

Bioaccumulative potential Bioaccumulation is unlikely.

## GAK8 Water based acrylic coating

### 12.4. Mobility in soil

Mobility No data available.

#### 2-Butoxyethanol

Mobility The product is miscible with water and may spread in water systems.

Surface tension 29.53 mN/m @ 20°C

### 12.5. Results of PBT and vPvB assessment

#### 2-Butoxyethanol

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

### 12.6. Other adverse effects

Other adverse effects None known.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

**Disposal methods** Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible.

## SECTION 14: Transport information

**General** For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

### 14.1. UN number

UN No. (ADR/RID) 3082

UN No. (IMDG) 3082

UN No. (ICAO) 3082

UN No. (ADN) 3082

### 14.2. UN proper shipping name

Proper shipping name (ADR/RID) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS 4,5-Dichloro-2-octyl-2H-isothiazol-3-one, 3-iodo-2-propynyl butylcarbamate)

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS 4,5-Dichloro-2-octyl-2H-isothiazol-3-one, 3-iodo-2-propynyl butylcarbamate)

## GAK8 Water based acrylic coating

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS 4,5-Dichloro-2-octyl-2H-isothiazol-3-one, 3-iodo-2-propynyl butylcarbamate)

Proper shipping name (ADN) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS 4,5-Dichloro-2-octyl-2H-isothiazol-3-one, 3-iodo-2-propynyl butylcarbamate)

### 14.3. Transport hazard class(es)

ADR/RID class	9
ADR/RID classification code	M6
ADR/RID label	9
IMDG class	9
ICAO class/division	9
ADN class	9

Transport labels



### 14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III
ICAO packing group	III

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



### 14.6. Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS	F-A, S-F
ADR transport category	3
Emergency Action Code	•3Z
Hazard Identification Number (ADR/RID)	90
Tunnel restriction code	(E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

**SECTION 15: Regulatory information**

## GAK8 Water based acrylic coating

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>National regulations</b>	Health and Safety at Work etc. Act 1974 (as amended). The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"]. EH40/2005 Workplace exposure limits.
<b>EU legislation</b>	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Commission Regulation (EU) No 2015/830 of 28 May 2015. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### Inventories

##### **EU - EINECS/ELINCS**

None of the ingredients are listed or exempt.

### **SECTION 16: Other information**

<b>Abbreviations and acronyms used in the safety data sheet</b>	ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways. RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail. IATA: International Air Transport Association. ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air. IMDG: International Maritime Dangerous Goods. CAS: Chemical Abstracts Service. ATE: Acute Toxicity Estimate. LC <sub>50</sub> : Lethal Concentration to 50 % of a test population. LD <sub>50</sub> : Lethal Dose to 50% of a test population (Median Lethal Dose). EC <sub>50</sub> : 50% of maximal Effective Concentration. PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative.
<b>Classification abbreviations and acronyms</b>	Aquatic Chronic = Hazardous to the aquatic environment (chronic)
<b>Classification procedures according to Regulation (EC) 1272/2008</b>	Aquatic Chronic 2 - H411: : Calculation method.
<b>Training advice</b>	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
<b>Issued by</b>	Toni Ashford
<b>Revision date</b>	18/07/2017
<b>Revision</b>	0
<b>SDS number</b>	1823

## GAK8 Water based acrylic coating

### Hazard statements in full

H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H330 Fatal if inhaled.  
H331 Toxic if inhaled.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H372 Causes damage to organs (Larynx) through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
EUH208 Contains 4,5-Dichloro-2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.